

		RGM 15	RGM 18	RGM 22	RGM 30	RGM 32	RGM 34
 Larghezza utile							
 Useful width	mm	1500	1800	2200	3000	3200	3400
 Anchura útil							
 Largeur utile							
 Dimensioni d'ingombro							
 Overall dimensions	mm	3800x1750 x2290	4100x1750 x2290	4500x1750 x2290	5300x1750 x2290	5500x1750 x2290	5700x1750 x2290
 Dimensiones ocupadas							
 Dimensions d'encombrement							
 Dimensioni di ingombro con paranco							
 Overall dimensions with hoist	mm	3800x3600 x3800	4100x3600 x3800	4500x3600 x3800	5300x3600 x3800	5500x3600 x3800	5700x3600 x3800
 Dimensiones ocupadas con aparejo							
 Dimensions d'encombrement avec poulie							
 Peso netto (con cilindro operativo)							
 Net weight (with operational cylinder)	kg	8700	10000	11700	15000	15800	16800
 Peso neto (con cilindro operativo)							
 Poids net (avec cylindre opérationnel)							
 Potenza installata							
 Installed power	kW	47	47	47	49	57	57
 Potencia instalada							
 Puissance installée							
 Potenza media assorbita							
 Average absorbed power	kW	27	27	28	30	30	30
 Promedio de la potencia absorbida							
 Puissance moyenne absorbée							
 Velocità regolabile							
 Adjustable speed	m/min	3÷25	3÷25	3÷25	3÷25	3÷25	3÷25
 Velocidad ajustable							
 Vitesse réglable							
 Temperatura max.							
 Maximum temperature	°C	180	180	180	180	180	180
 Temperatura máx.							
 Température max.							
 Pressione lineare bassa							
 Low linear pressure	kg/cm	1÷45	1÷45	1÷45	1÷45	1÷45	1÷45
 Presión lineal baja							
 Pression linéaire basse							
 Pressione lineare alta							
 High linear pressure	kg/cm	45÷250	45÷250	45÷250	45÷250	45÷250	45÷250
 Presión lineal alta							
 Pression linéaire haute							

