

| | | RTP 15 | RTP 18 | RTP 22 | RTP 26 | RTP 30 | RTP 32 | RTP 34 |
|--|--|--------|-----------|-----------|-----------|-----------|-----------|-----------|
| | Larghezza utile | | | | | | | |
| | Useful width | mm | 1500 | 1800 | 2200 | 2600 | 3000 | 3400 |
| | Anchura útil | | | | | | | |
| | Largeur utile | | | | | | | |
| | Dimensioni d'ingombro | | | | | | | |
| | Overall dimensions | mm | 2860x2030 | 3160x2030 | 3560x2030 | 3960x2030 | 4360x2030 | 4560x2030 |
| | Dimensiones ocupadas | | x1650 | x1650 | x1650 | x1650 | x1650 | x1650 |
| | Dimensions d'encombremet | | | | | | | |
| | Peso netto (senza cilindro riscaldato) | | | | | | | |
| | Net weight (without heated cylinder) | kg | 5600 | 5800 | 6200 | 7400 | 8600 | 9200 |
| | Peso neto (sin cilindro calentado) | | | | | | | |
| | Poids net (sans cylindre chauffé) | | | | | | | |
| | Potenza installata | | | | | | | |
| | Installed power | kW | 49 | 49 | 49 | 49 | 49 | 49 |
| | Potencia instalada | | | | | | | |
| | Puissance installée | | | | | | | |
| | Potenza media assorbita | | | | | | | |
| | Average absorbed power | kW | 22 | 22 | 22 | 22 | 22 | 22 |
| | Promedio de la potencia absorbida | | | | | | | |
| | Puissance moyenne absorbée | | | | | | | |
| | Velocità regolabile | | | | | | | |
| | Adjustable speed | m/min | 3÷25 | 3÷25 | 3÷25 | 3÷25 | 3÷25 | 3÷25 |
| | Velocidad ajustable | | | | | | | |
| | Vitesse réglable | | | | | | | |
| | Temperatura regolabile | | | | | | | |
| | Adjustable temperature | °C | 1÷180 | 1÷180 | 1÷180 | 1÷180 | 1÷180 | 1÷180 |
| | Temperatura ajustable | | | | | | | |
| | Température réglable | | | | | | | |
| | Pressione | | | | | | | |
| | Pressure | kg/cm | 0÷250 | 0÷250 | 0÷250 | 0÷250 | 0÷250 | 0÷250 |
| | Presión | | | | | | | |
| | Pression | | | | | | | |

